

SMOKY LAKE COUNTY



Title: Risk Control: Odorant-Mercaptan	Policy No.: C.02-01
Section: 14	Page No.: 1 of 12 E

Legislation Reference:	Municipal Government Act, Chapter M26.1 – Section 201.
-------------------------------	--

Purpose:	To provide a risk assessment for the usage of Mercaptan for odorization in Natural Gas.
-----------------	---

Policy Statement and Guidelines:	
1. <u>Definition:</u>	
Mercaptan (Methyl ethyl sulfide):	A clear liquid, Sentinal 20, which is vaporized into Natural Gas mainly to be able to detect gas leaks for safety. This product is listed in the Toxic Substances Control (TSCA) Inventory of Chemicals; hence it may be subject to applicable TSCA provisions and restrictions along with all Canadian federal regulations. This product is manufactured in the US (Texas) and trucked into Canada.
2. <u>Uses for Mercaptan:</u>	
2.1	It is a repulsive smelling, clear liquid placed into tanks at R.M.O.: Regulating, Metering and Odorizing stations, where gas can flow through, vaporizing the Mercaptan, making the Natural Gas smell detectable.
3. <u>Mercaptan: Safety a Primary Concern</u>	
A. <u>Primary Risk Situation:</u>	
3.1	Delivery of odorant to Bulk facilities (storage tanks).
3.2	Transfer of odorant from bulk facilities to truck skid.
3.3	Delivery of odorant from truck skid into Odorizer. (RMO)

Title: Risk Control: Odorant-Mercaptan	Policy No.: C.02-01
Section: 14	Page No.: 2 of 12 E

Policy Statement and Guidelines:

B. Safety Measures:

- 3.4 Needs to be handled by certified personnel with Sentinel 20 Mercaptan training.
- 3.5 Must have Dangerous Goods Certification.
- 3.6 It is a class 3 flammable liquid which requires the vehicle to be placard.
- 3.7 In concentrations of more than 1 ppm, air purification respirators should be used.
- 3.8 Where splashing may occur, eyes and skin should be protected. (gloves, long sleeves, goggles, face mask). Treatment as per ***Schedule "A": Material Safety Data Sheet (MSDS)***.
- 3.9 Incompatible with oxygen and strong oxidizing materials.
- 3.10 Properly sealed containers will be stored in a well ventilated building.
- 3.11 Fire extinguishing media:
 - a. Dry Chemical
 - b. Foam
 - c. Carbon Dioxide

4. Environment Impact of Mercaptan

4.1 Risk Spill Factor

- Due to Mercaptan's strong odor, and the high publicity a spill would receive, it is imperative for any Mercaptan spill treatment to abide strictly by regulations. Procedures detailed in RMO emergency response procedures under **Section 2.0 – 10.0: "Guidelines for Operation and Maintenance Practices"** in the Alberta Natural Gas Utilities.
- The odorant contractor (Smoky Lake Natural Gas Utility) should be immediately made aware of any odorant spill they may not be aware of.
- The odorant contractor (Smoky Lake Natural Gas Utility) will review the spill and, if required, implement the spill containment contractor, (CEDA). As time is of the essence, if the odorant contractor delegates this responsibility to the rural utility, they can implement the spill containments contractor.


Title: Risk Control: Odorant-Mercaptan	Policy No.: C.02-01
Section: 14	Page No.: 3 of 12 E

Policy Statement and Guidelines:	
4.2	<p>Disposal</p> <ul style="list-style-type: none"> • Mercaptan waste material shall be disposed of through an approved and licensed hazardous waste disposal facility, and in accordance with Federal, Provincial and local regulations. Generally, the spill containments contractor (CEDA) will handle this process for the rural utility.
5. <u>Summary</u>	
<ul style="list-style-type: none"> • <u>Low risk factor:</u> <ul style="list-style-type: none"> ▪ Mercaptan poses a low risk factor when handled by trained personnel with the proper protective equipment. • <u>High risk factor:</u> <ul style="list-style-type: none"> ▪ Mercaptan leakage – risk control is to contact the following authorities. ▪ Contact immediately: <ul style="list-style-type: none"> ○ Alberta Federation of Gas-Co-ops ○ CEDA • <u>Contact emergency Phone Numbers:</u> <ul style="list-style-type: none"> ▪ Contact local authority and local gas companies. ▪ Phillips Chemical Company (Supplier) <ul style="list-style-type: none"> ○ Emergency: (918) 661-8118 ○ Technical Services: (918) 661-9091 ▪ Smoky Lake County Gas (Utility) <ul style="list-style-type: none"> ○ Office: (780) 656-3037 ○ Emergency: (780) 650-1500 ▪ Federation of Alberta Gas Co-ops <ul style="list-style-type: none"> ○ On Call (780) 416-6543 ▪ CEDA (Spill Containments Contractor) <ul style="list-style-type: none"> ○ Emergency (780) 472-6766 	

	Date	Resolution Number
Approved	September 20, 2007	# 596-07 - Page # 8453
Amended		
Amended		



Material Safety Data Sheet



SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Scentinel® F-20 Gas Odorant

Product Use: Odorant

Product Number(s): 0001024691, 0001024690, 0001024694, 0001024693, 0001024692, 0001024789, 0001087135

Synonyms: Mercaptan Mixture; Gas Odorant

Product Cas No.: Mixture

Company Identification:

Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands TX 77380

Product Information:

MSDS Requests: (800) 852 - 5530
Technical Information: (832) 813 - 4862

24-Hour Emergency Telephone Numbers

HEALTH: Chevron Phillips Emergency Information Center 866.442.9628 (North America) and 1.832.813.4984 (International)

TRANSPORTATION: North America: CHEMTREC 800.424.9300 or 703.527.3887

ASIA: +1.703.527.3887

EUROPE: BIG .32.14.584545 (phone) or .32.14.583516 (telefax)

SOUTH AMERICA SOS-Cotec Inside Brazil: 0800.111.767

Outside Brazil: 55.19.3467.1600

SECTION 2 COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENT	CAS NUMBER	AMOUNT	EINECS	SYM	R-PHRASES
Tertiary Butyl Mercaptan	75-66-1	79 % weight	200-890-2	F Xn	R65, R43, R51, R11
Dimethyl Sulfide	75-18-3	20 % weight	200-846-2	F Xn	R36, R65, R52, R11
Related Materials	Various	1 % weight	NA	NA	NA

Occupational Exposure Limits:

Revision Number: 4
Revision Date: 02/06/2006

1 of 9

Scentinel® F-20 Gas Odorant
MSDS : 34930

Component	Limit	TWA	STEL	Ceiling / Peak	Notation
Dimethyl Sulfide	ACGIH	10 ppm	NA	NA	NA
Dimethyl Sulfide	CPCHEM	10 ppm	NA	NA	NA
Tertiary Butyl Mercaptan	ACGIH	Not Established	NA	NA	n-Butyl Mercaptan: 0.5 ppm
Tertiary Butyl Mercaptan	CPCHEM	.5 ppm	NA	NA	As n-Butyl Mercaptan

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Clear liquid, repulsive odor.

- HIGHLY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE
- HARMFUL OR FATAL IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE
- MAY CAUSE SKIN IRRITATION
- MAY CAUSE NAUSEA, DIZZINESS, OR HEADACHE
- CAUSES EYE IRRITATION
- MAY CAUSE AN ALLERGIC SKIN REACTION
- TOXIC TO AQUATIC ORGANISMS

IMMEDIATE HEALTH EFFECTS:

Eye: Contact with the eyes causes irritation. Symptoms may include pain, tearing, reddening, swelling and impaired vision.

Skin: This material may be irritating to the skin. The degree of the injury will depend on the amount of material that gets onto the skin and the speed and thoroughness of the first aid treatment. Contact with the skin may cause an allergic skin reaction. Symptoms may include pain, itching, discoloration, swelling, and blistering. Not expected to be harmful to internal organs if absorbed through the skin.

Ingestion: This material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death. May be irritating to mouth, throat, and stomach. Symptoms may include nausea, vomiting, and diarrhea.

Inhalation: Not expected to be harmful if inhaled. This material has a strong objectionable odor that may cause nausea, dizziness, or headache.

SECTION 4 FIRST AID MEASURES

Eye: Flush eyes with running water immediately while holding the eyelids open. Remove contact lenses, if worn, after initial flushing, and continue flushing for at least 15 minutes. Get immediate medical attention.

Skin: To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse. Get medical attention if any symptoms develop.

Ingestion: If swallowed, do not induce vomiting. Give the person a glass of water or milk to drink and get immediate medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms continue.

Note to Physicians: Ingestion of this product or subsequent vomiting may result in aspiration of light hydrocarbon liquid, which may cause pneumonitis.

SECTION 5 FIRE FIGHTING MEASURES

Revision Number: 4
Revision Date: 02/06/2006

2 of 9

Scentine® F-20 Gas Odorant
MSDS : 34930

See Section 7 for proper handling and storage.

FIRE CLASSIFICATION:

OSHA Classification (29 CFR 1910.1200): Flammable liquid.

NFPA RATINGS: Health: 2 Flammability: 3 Reactivity: 0

FLAMMABLE PROPERTIES:

Flashpoint: < -18°C (< -0.4°F) Estimated

Autoignition: NDA

Flammability (Explosive) Limits (% by volume in air): Lower: NDA Upper: NDA

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions: For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Eliminate all sources of ignition in the vicinity of the spill or released vapor. If this material is released into the work area, evacuate the area immediately. Monitor area with combustible gas indicator. Wear appropriate personal protective equipment when cleaning up spills. Refer to Section 8.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible sorbent materials or pumping. All equipment used when handling the product must be grounded. A vapor suppressing foam may be used to reduce vapors. Use clean non-sparking tools to collect absorbed material. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Spill residues and contaminated soil may be deodorized using dilute (5%) aqueous solutions of bleach (sodium hypochlorite). Alternatively, household bleach (Clorox, Purex) in a dilute solution may be used. Do not use concentrated or dry bleach. Absorb in dry, inert material. Do not attempt to neutralize or deodorize bulk liquid mercaptan. Concentrated bleach will cause heating and possible ignition. Attempts to neutralize bulk liquid mercaptan with bleach solutions will be ineffective and only serve to increase the amount of liquid to dispose.

Reporting: U.S.A. regulations require reporting spills of this material that could reach any surface waters. Report spills to local authorities and/or the National Response Center at (800) 424-8802 as appropriate or required.

SECTION 7 HANDLING AND STORAGE

READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL . REFER TO PRODUCT LABEL OR MANUFACTURERS TECHNICAL BULLETINS FOR THE PROPER USE AND HANDLING OF THIS MATERIAL .

Precautionary Measures: This material presents a fire hazard. Liquid quickly evaporates and forms vapor (fumes) which can catch fire and burn with explosive violence. Invisible vapor spreads easily and can be set on fire by many sources such as pilot lights, welding equipment, and electrical motors and switches. Fire hazard is greater as liquid temperature rises above 15°F. Avoid breathing vapors or fumes which may be released during thermal processing. Do not get in eyes.

General Handling Information: Avoid work practices that may release volatile components in the atmosphere. Local air

Revision Number: 4

3 of 9

Scentinel® F-20 Gas Odorant

Revision Date: 02/06/2006

MSDS : 34930

pollution regulations should be consulted to determine if the release of volatile components is regulated or restricted in the area in which this material is used. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations, which have the potential of generating an accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids, National Fire Protection Association (NFPA 77), Recommended Practice on Static Electricity' (liquids, powders and dusts), and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents' (liquids).

General Storage Information: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner, or disposed of properly. **DO NOT USE OR STORE** near heat, sparks or open flames. **USE AND STORE ONLY IN WELL VENTILATED AREA.** Keep container closed when not in use.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 3) applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

ENGINEERING CONTROLS:

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits. Use in a well-ventilated area. If heated material generates vapor or fumes, use process enclosures, local exhaust ventilation, or other engineering controls to control exposure.

PERSONAL PROTECTIVE EQUIPMENT:

Eye/Face Protection: Wear eye protection such as safety glasses, chemical goggles, or faceshields if engineering controls or work practices are not adequate to prevent eye contact.

Skin Protection: Wear impervious protective clothing to prevent skin contact. Selection of protective clothing may include gloves, apron, boots, and complete facial protection depending on operations conducted. Users should determine acceptable performance characteristics of protective clothing. Consider physical requirements and other substances present when selecting protective clothing. Suggested materials for protective gloves include: Silver Shield, or Viton

Respiratory Protection: If exposure is anticipated to be greater than applicable exposure limits, wear a NIOSH approved respirator that provides adequate protection from measured concentrations of this material. Use the following elements for air-purifying respirators: Air-Purifying Respirator for Organic Vapors

Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection. Air-purifying respirators are not

Revision Number: 4
Revision Date: 02/06/2006

4 of 9

Scentinel® F-20 Gas Odorant
MSDS : 34930

recommended due to potential olfactory fatigue.

Occupational Exposure Limits:

Component	Limit	TWA	STEL	Ceiling / Peak	Notation
Dimethyl Sulfide	ACGIH	10 ppm	NA	NA	NA
Dimethyl Sulfide	CPCHEM	10 ppm	NA	NA	NA
Tertiary Butyl Mercaptan	ACGIH	Not Established	NA	NA	n-Butyl Mercaptan: 0.5 ppm
Tertiary Butyl Mercaptan	CPCHEM	.5 ppm	NA	NA	As n-Butyl Mercaptan

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear liquid, repulsive odor.

pH: NA

VAPOR PRESSURE: 8.2 psia Estimated @ 38 °C (100.4°F)

VAPOR DENSITY (AIR=1): >2

BOILING POINT: 48.9°C (120.02°F) - 93.3°C (199.94°F)

SOLUBILITY (in water): Negligible

PERCENT VOLATILE: 100 % volume

FREEZING POINT: <-45.6°C (-50.08°F)

SPECIFIC GRAVITY: 0.816 @ 15.6 °C (60°F)

DENSITY: 6.79 lb/gal @ 15.6 °C (60°F)

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Conditions to Avoid: Not Applicable

Incompatibility With Other Materials: No data available

Hazardous Decomposition Products: Carbon Oxides. Sulfur Oxides.

Hazardous Polymerization: Hazardous polymerization will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

IMMEDIATE HEALTH EFFECTS:

Acute Oral Toxicity: Tertiary Butyl Mercaptan: LD50 / rat / 8.4 g/kg

Acute Dermal Toxicity: Tertiary Butyl Mercaptan: LD50 / rabbit / 20.8 g/kg

Acute Inhalation Toxicity: Tertiary Butyl Mercaptan: LC50 / rat / 26,432 ppm / 4 hour(s)

Eye Irritation: Dimethyl Sulfide: This material is irritating to the eyes.

Skin Irritation: Dimethyl Sulfide: May cause skin irritation.

Sensitization: Dermal / sensitizer / guinea pig / (based on test results for the components)

ADDITIONAL TOXICOLOGY INFORMATION:

This product contains TERTIARY BUTYL MERCAPTAN:

Revision Number: 4

Revision Date: 02/06/2006

5 of 9

Scentinel® F-20 Gas Odorant

MSDS : 34930

Repeated Dose Toxicity: 13 weeks / Inhalation / rat / Doses 0, 9, 97 or 196ppm / 6 h/day, 5 days/week /LOAEL = 9ppm (proximal tubular nephrosis was observed in male rats only)
 Reproductive and Developmental Toxicity: GD 6-16 / inhalation / mice / Doses: 0, 11, 99 or 195ppm (atmospheric concentration) / 6hr/day / NOAEL = 195ppm (no teratology effects were observed); GD 6-19 / inhalation / rat / Doses: 0, 11, 99 or 195ppm (atmospheric concentration) / 6hr/day / NOAEL = 9ppm (no teratology effects were observed)
 Genetic Toxicity: Ames test - negative; Sister Chromatid Exchange Assay - negative; Mouse lymphoma forward mutational assay - positive; Mouse micronucleus assay - negative

This product contains DIMETHYL SULFIDE.

Repeated Dose Toxicity: 14 weeks/ gavage / rat /Doses (0, 2.5, 25, 250 mg/kg/day) / NOAEL >= 250 mg/kg/day

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY:

This material is expected to be toxic to aquatic organisms.

Tertiary Butyl Mercaptan - 48 hour(s) / EC50 / water flea (*Daphnia magna*) / 6.7 mg/l

Tertiary Butyl Mercaptan - 96 hour(s) / LC50 / rainbow trout (*Salmo gairdneri*) / 34 mg/l

Dimethyl Sulfide - 48 hour(s) / EC50 / water flea (*Daphnia magna*) / 23 mg/l

Tertiary Butyl Mercaptan - 72 hour(s) / EC50 / green algae (*Selenastrum capricornutum*) / 24 mg/l

ENVIRONMENTAL FATE:

This material is expected to be readily biodegradable.

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

Shipping Descriptions per regulatory authority.

US DOT

MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (tert-Butyl Mercaptan and Dimethyl Sulfide), 3, UN3336, II

ICAO / IATA

MERCAPTANS, LIQUID, FLAMMABLE, N.O.S. , (tert-Butyl Mercaptan and Dimethyl Sulfide), 3, UN3336, II

IMO / IMDG

MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (tert-Butyl Mercaptan and Dimethyl Sulfide), 3, UN3336, II, (-18°C)

Revision Number: 4
 Revision Date: 02/06/2006

6 of 9

Scentinel® F-20 Gas Odorant
 MSDS : 34930

RID / ADR

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (tert-Butyl Mercaptan and Dimethyl Sulfide), 3, II, ADR

SECTION 15 REGULATORY INFORMATION

SARA 311/312 CATEGORIES:	1. Immediate (Acute) Health Effects:	YES
	2. Delayed (Chronic) Health Effects:	NO
	3. Fire Hazard:	YES
	4. Sudden Release of Pressure Hazard:	NO
	5. Reactivity Hazard:	NO

REGULATORY LISTS SEARCHED:

01 = CA Prop 65	17 = FDA 178	33 = RCRA Waste Appendix VIII
02 = LARTK	18 = FDA 179	34 = RCRA Waste D-List
03 = MARTK	19 = FDA 180	35 = RCRA Waste P-List
04 = MN Hazardous Substance	20 = FDA 181	36 = RCRA Waste U-List
05 = NJ RTK	21 = FDA 182	37 = SARA Section 311/312
06 = PARTK	22 = FDA 184	38 = SARA Section 313
07 = CAA Section 112 HAPs	23 = FDA 186	39 = TSCA 12 (b)
08 = CWA Section 307	24 = FDA 189	40 = TSCA Section 4
09 = CWA Section 311	25 = IARC Group 1	41 = TSCA Section 5(a)
10 = DOT Marine Pollutant	26 = IARC Group 2A	42 = TSCA Section 8(a) CAIR
11 = FDA 172	27 = IARC Group 2B	43 = TSCA Section 8(a) PAIR
12 = FDA 173	28 = IARC Group 3	44 = TSCA Section 8(d)
13 = FDA 174	29 = IARC Group 4	45 = WHIMS - IDL
14 = FDA 175	30 = NTP Carcinogen	46 = Germany D TAL
15 = FDA 176	31 = OSHA Carcinogen	47 = Germany WKG
16 = FDA 177	32 = OSHA Highly Hazardous	48 = DEA List 1
		49 = DEA List 2

The following components of this material are found on the regulatory lists indicated.

Tertiary Butyl Mercaptan	3, 5, 6, 46
Dimethyl Sulfide	3, 5, 6, 46

CERCLA REPORTABLE QUANTITIES(RQ)/SARA 302 THRESHOLD PLANNING QUANTITIES(TPQ):

Component	Component RQ	Component TPQ	Product RQ
Dimethyl Sulfide	100 lbs	None	500 lbs
Tertiary Butyl Mercaptan	100 lbs	None	126 lbs

WHMIS CLASSIFICATION:

Class B, Division 2: Flammable Liquids

Class D, Division 2, Subdivision B: Toxic Material

Revision Number: 4
Revision Date: 02/06/2006

7 of 9

Scentinel® F-20 Gas Odorant
MSDS : 34930

Skin Sensitization
Skin or Eye Irritation

CHEMICAL INVENTORY LISTINGS:

AUSTRALIA: All the components of this material are listed on the Australian Inventory of Chemical Substances (AICS).

CANADA: All the components of this material are on the Canadian Domestic Substances List (DSL).

PEOPLE'S REPUBLIC OF CHINA: All the components of this product are listed on the draft Inventory of Existing Chemical Substances in China.

EUROPEAN UNION: All the components of this material are in compliance with the EU Seventh Amendment Directive 92/32/EEC.

JAPAN: All the components of this product are on the Existing & New Chemical Substances (ENCS) inventory in Japan, or have an exemption from listing.

KOREA: All the components of this product are on the Existing Chemicals List (ECL) in Korea.

PHILIPPINES: All the components of this product are listed on the Philippine Inventory of Chemicals and Chemical Substances (PICCS).

UNITED STATES: All of the components of this material are on the Toxic Substances Control Act (TSCA) Chemical Inventory.

EU RISK AND SAFETY PHRASES:

R11: Highly flammable.

R36: Irritating to eyes.

R43: May cause sensitization by skin contact.

R51: Toxic to aquatic organisms.

R65: Harmful: may cause lung damage if swallowed.

S2: Keep out of the reach of children.

S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking.

S24: Avoid contact with skin.

S25: Avoid contact with eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S51: Use only in well-ventilated areas.

S62: If swallowed do not induce vomiting: seek medical advice immediately and show this container or label.

S36/37: Wear suitable protective clothing and gloves.

EU Symbols: Xn - Harmful F - Flammable

SECTION 16 OTHER INFORMATION

NFPA RATINGS: Health: 2 Flammability: 3 Reactivity: 0 Special: NA

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA).

REVISION STATEMENT: This revision updates all sections of the MSDS please review.

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

Revision Number: 4
Revision Date: 02/06/2006

8 of 9

Scintinel® F-20 Gas Odorant
MSDS : 34930

TLV	Threshold Limit Value	TWA	- Time Weighted Average
STEL	- Short-term Exposure Limit	PEL	- Permissible Exposure Limit
ACGIH	- American Conference of Government Industrial Hygienists	OSHA	- Occupational Safety & Health Administration
NIOSH	- National Institute for Occupational Safety & Health	NFPA	- National Fire Protection Agency
WHMIS	- Workplace Hazardous Materials Information System	IARC	- Intl. Agency for Research on Cancer
EINECS	- European Inventory of existing Commercial Chemical Substances	RCRA	- Resource Conservation Recovery Act
SARA	- Superfund Amendments and Reauthorization Act.	TSCA	- Toxic Substance Control Act
EC50	- Effective Concentration	LC50	- Lethal Concentration
LD50	- Lethal Dose	CAS	- Chemical Abstract Service
NDA	- No Data Available	NA	- Not Applicable
<=	- Less Than or Equal To	>=	- Greater Than or Equal To
CNS	- Central Nervous System	MAK	- Germany Maximum Concentration Values

**This data sheet is prepared according to the latest adaptation of the EEC Guideline 67/548.
This data sheet is prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200).
This data sheet is prepared according to the ANSI MSDS Standard (Z400.1).
This data sheet was prepared by EHS Product Stewardship Group, Chevron Phillips Chemical Company LP, 10001 Six Pines Drive, The Woodlands, TX 77380.**

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.